

Question

[Eduard Lebedyuk](#) · Oct 5, 2017

Java Gateway - How to store object in memory between calls?

Trying to connect Ensemble to RabbitMQ following this [article](#) I'm using Java Gateway and encountered the following problem - in all my calls I need to pass connection object, which is always the same but it takes a long time to create. Here's java code:

```
package com.myorgname.rabbitmq;

import com.rabbitmq.client.ConnectionFactory;
import com.rabbitmq.client.Connection;
import com.rabbitmq.client.Channel;
import com.rabbitmq.client.QueueingConsumer;

public class Wrapper {

    public void sendMsg(String hostName, String queueName, byte[] msg) throws Exception
    {
        ConnectionFactory factory = new ConnectionFactory();
        factory.setHost(hostName);
        Connection connection = factory.newConnection();
        Channel channel = connection.createChannel();
        channel.queueDeclare(queueName, false, false, false, null);

        channel.basicPublish("", queueName, null, msg);

        channel.close();
        connection.close();
    }

    public int readMsg(String hostName, String queueName, byte[] msg) throws Exception
    {
        ConnectionFactory factory = new ConnectionFactory();
        factory.setHost(hostName);
        Connection connection = factory.newConnection();
        Channel channel = connection.createChannel();
        channel.queueDeclare(queueName, false, false, false, null);
        QueueingConsumer consumer = new QueueingConsumer(channel);
        channel.basicConsume(queueName, true, consumer);

        QueueingConsumer.Delivery delivery = consumer.nextDelivery();
        int len = delivery.getBody().length;
        System.arraycopy(delivery.getBody(), 0, msg, 0, len);

        channel.close();
        connection.close();

        return len;
    }
}
```

```
}
```

As you see to publish or to get a message a new connection is made each time.

I'm interested in a way to create a connection object only once and use it to send several messages. Is it possible?

[#Ensemble](#) [#Interoperability](#) [#Java](#)

Source URL: <https://community.intersystems.com/post/java-gateway-how-store-object-memory-between-calls>