

## Question

[Paul Riker](#) · Apr 24, 2018

## Custom Purge Job

I want to create an interface specific purge job. Please let me know if there are any holes in my approach. I realize that an interface that went from HospitalAService to HospitalARouter to PracticeBOperation would require two separate executes in my example below, but I want that granularity as there are some intermediate steps in our workflows that we don't need to retain messages for.

1. Create a custom scheduled task that extends Ens.MessageHeader
2. Overwrite the Purge function select statements

## a. Integrity

## i. Old

```

■ DECLARE C1 CURSOR FOR
  Select TOP 100000000 ID,MessageBodyId,MessageBodyClassName Into :%tID,:%t
  BodyId,:%tBodyClassname From Ens.MessageHeader h
  Where (TimeCreated < :%tDoNotDeleteDate)
  And 0 = ( Select Count(*) From Ens.MessageHeader
  Where (SessionId = h.SessionId)
  And (Status<>$$$eMessageStatusCompleted)
  And (Status<>$$$eMessageStatusAborted)
  And (Status<>$$$eMessageStatusError)
  And (Status<>$$$eMessageStatusDiscarded)
  Order By TimeCreated
  )

```

## ii. New

```

DECLARE C1 CURSOR FOR
  Select TOP 100000000 ID,MessageBodyId,MessageBodyClassName Into :%tID,:%t
  BodyId,:%tBodyClassname From Ens.MessageHeader h
  Where SourceConfigName=:tSourceConfigName and TargetConfigName =
  :tTargetConfigName and (TimeCreated < :%tDoNotDeleteDate)
  And 0 = ( Select Count(*) From Ens.MessageHeader
  Where (SessionId = h.SessionId)
  And (Status<>$$$eMessageStatusCompleted)
  And (Status<>$$$eMessageStatusAborted)
  And (Status<>$$$eMessageStatusError)
  And (Status<>$$$eMessageStatusDiscarded)
  And SourceConfigName = :tSourceConfigName
  And TargetConfigName = :tTargetConfigName

```

•

```

Order By TimeCreated
)

```

## b. No Integrity

## i. Old

```

DECLARE C2 CURSOR FOR

```

```

  Select ID,MessageBodyId,MessageBodyCla
  ssName Into :%tID,:%tBodyId,:%tBodyClassname From Ens.MessageHeader
  Where SourceConfigName=:tSourceConfigName and TargetConfigName =
  :tTargetConfigName and (TimeCreated < :%tDoNotDeleteDate))

```

## ii. New

```

DECLARE C2 CURSOR FOR

```

```
                Select ID,MessageBodyId,MessageBodyClass  
                Name Into :%tID,:%tBodyId,:%tBodyClassname From Ens.MessageHeader  
                Where SourceConfigName=:tSourceConfigName and TargetConfigName =  
                :tTargetConfigName and (TimeCreated < :%tDoNotDeleteDate))
```

[#System Administration](#) [#Ensemble](#)

---

Source URL:<https://community.intersystems.com/post/custom-purge-job>