Question
Peter N · Jul 11, 2020

Backspace in WebTerminal

I try to run a small test routine (guessing a random number) in WebTerminal but the result looks broken.
in IRISterminal:

```
USER>d ^guess

1         .>.....*..    guess [0..9]: 1
2         ..>.....*.    guess [0..9]: 2
3         ..........    guess [0..9]: c !no number
```

in WebTerminal:

```
USER > d ^guess

1         .>...*....    guess [0..9]: 1
2         ..>......*    guess [0..9]: 2
3         ..........    guess [0..9]: a !no numberb !no numberc !no number
```

I think it relates to backspace.
Is there some special setting required?

The code:

```
a
 s q="..........  guess [0..9]: "
 f i=1:1 d b if p w ! w $c(9),"thank you",! q
 q
b
 w !,i,$c(9),q
 f  r v#1 q:(v?.1n) w " !no number",$c(8,8,8,8,8,8,8,8,8,8,8,8)
 w " "
 s r=$R(10),p=$s(v="":1,v=r:"!",v>r:"<",1:">")
 s x=q,$e(x,r+1)="*",$e(x,v+1)=$s(v=r:"!",v>r:"<",1:">")
 q:p  w $c(13),$c(9),x s p=v=r q
```

#ObjectScript #Terminal #InterSystems IRIS

Source URL:https://community.intersystems.com/post/backspace-webterminal