Question
Roger Taylor · Jun 8, 2021

LDAP.mac -- Why use $$$WindowsCacheClient instead of $$$ISWINDOWS?

Reference: sample LDAP code routine **LDAP.mac**

Some IF statements reference macro **$$$WindowsCacheClient** as a boolean flag to mark if the client calling the LDAP server is running Windows. Other IF statements reference **$$$ISWINDOWS**. Are they not the same thing? That is, does the routine need $$$WindowsCacheClient at all?

Examples:

```
#define WindowsCacheClient 1

if $$$WindowsCacheClient,$$$WindowsLDAPServer {
s Status=##Class(%SYS.LDAP).Binds(LD,"",$lb(Username,Domain,Password),$$$LDAPAUTHNEGOTIATE)
i Status'=$$$LDAPSUCCESS {
s Status=Status_",ldapBinds(AdminDN) - "  _##Class(%SYS.LDAP).Err2String(Status)
g Done
  }

i $$$ISWINDOWS,$$$UseSecureConnection {
s LD=##Class(%SYS.LDAP).Init($$$LDAPServer,636)
 } else {
s LD=##Class(%SYS.LDAP).Init($$$LDAPServer)
 }
```

#LDAP #Caché #InterSystems IRIS
Product version: IRIS 2020.1
$ZV: IRIS for Windows (x86-64) 2020.1 (Build 217U) Tue May 26 2020 20:41:06 EDT

Source URL:https://community.intersystems.com/post/ldapmac-why-use-windowscacheclient-instead-iswindows