
Question

[Joost Platenburg](#) · Feb 17, 2022

Creating an OAuth2 server from code

LS,

Is there a samples on how to create the OAuth2 server from code? Now trying:

```
set oauth2server = ##class(OAuth2.Server.Configuration).%New()
set oauth2server.Key = "singleton"
set oauth2server.IssuerEndpoint = "https://localhost:52773/oauth2"
set oauth2server.Description = "MedMij Authorization Server"
set oauth2server.AccessTokenInterval = 900
set oauth2server.AuthorizationCodeInterval = 900
set oauth2server.RefreshTokenInterval = 3600
set oauth2server.SessionInterval = 3600
set oauth2server.ClientSecretInterval = 0
set oauth2server.SupportedScopes = "ikp-scope"
set oauth2server.DefaultScope = "ikp-scope"
set oauth2server.AllowUnsupportedScope = 1
set oauth2server.SupportedGrantTypes = "A"
set oauth2server.SSLConfiguration = "MedMij Oauth2Server"
set sc = oauth2server.%Save()
```

[#OAuth2](#) [#InterSystems IRIS for Health](#)

Product version: IRIS 2022.1

\$ZV: IRIS for UNIX (Ubuntu Server LTS for ARM64 Containers) 2021.1 (Build 215U) Wed Jun 9 2021 13:47:40 UTC

Source URL:<https://community.intersystems.com/post/creating-oauth2-server-code>